

NOT JUST SIGNAL TRANSMISSION. THIS IS SIGNAL SUPREMACY.

Latency	Down to 45 ms in HD and 75 ms in 4K
Link capacity	Maximum 100 Mbps

Encoder MT-102V

High efficiency dual channel encoder in Mil Spec rugged housing with integrated connector protection bars

Integrated 5 port 10/100 Mbit Ethernet switch

Dual channel HEVC and H.264

Encodes and streams 2x HD/SD sources simultaneously, or 1x4K channel

2 channels with encoding resolutions up to 3840x2160p60 total, frame scaling and frame rate range 1-60, low latency encoding

1x12G-SDI, 1x3G-SDI and 1x analogue stereo audio input

UDP TS, RTP TS/ES, RTMP and error correction (Zixi / Pro-MPEG / SRT) protocols

AES encryption (128/256-bit)

CVBS Optional

RF

MIMO Techniques	Spatial multiplexing, space-time coding, TX/RX Eigen Beamforming
Output power	1 mW - 10 W (up to 20 W effective w/TX Beamforming)
Channel BW	5-10-20 MHz
Available freq bands	400 MHz to 6 GHz (See radio datasheet for details)

Mechanical

	Encoder	Radio SC4200
Size (h x w x d)	130 x 100 x 48 mm	101 x 67 x 38 mm
Weight	725 g	425 g
IP rating	IP67	IP68
Material	Black or natural anodized aluminium	Black anodized aluminium
Temp range	-40 to +65°C	-40 to +65°C

Power

Power consumption	9 W	5-16 W @ 1 W TX power
		5-24 W @ 4 W TX power
Voltage	9-20V DC, internal DC/DC converter with reverse polarity, overvoltage & undervoltage protection	9-20 V DC
Power options	Fed from ext. battery	Fed from encoder
Status indicator	Green LED	Multicolour LED

Interfaces

Primary cable	Mil Spec IP68 10 pin connector> ODU primary cable Silvus (power, ETH, RS232), 30 cm or 2 m
	Mil-Spec IP68 22 pin connector> $5 \times \text{Switchcraft connector (power in, } 2 \times \text{Ethernet, RS232, audio),} 30 cm. Compatible with Silvus SC 4200 / 4400$
Video	2x Amphenol HD BNC

3 ELEMENTS

THREE ELEMENTS MEDIA GMBH FREIHEIT 15 13597 BERLIN PHONE: +49 30 403 655 660

THREE ELEMENTS ITALY SRL PIAZZA DELLA DOGANA 4 39100 BOLZANO ITALY THREE ELEMENTS CAPE TOWN LTD 37 SILVERSTONE RD. KILLANY GARDENS CAPETOWN 7441